

Randall Industrial Curtains



Dock Enclosures



Spray Booth Curtains



High Temperature/Welding Curtains

Contain it!

Work Areas, Fumes, Hazardous Materials, and Outside Elements

Randall Industrial Curtains help organizations quickly divide work areas, contain a variety of air-borne particles, odors, UV flash and welding sparks.

Improve working conditions and productivity with easy to install, economical Randall Industrial Curtains. Flame retardant vinyl is compliant with California Fire Marshal, NFPA-701, and ASTM-E84 standards.

Experienced Team

Our team brings over 20 years of industry experience to your project. We can work with you to design the best solution for your application.

Custom Applications

We specialize in designing and manufacturing applications that are considered by many as too difficult or out of the ordinary.

Turnkey Project Management

Randall excels at managing the details. We coordinate your project through each stage of development, manufacture, and installation, if needed.

Randall Industrial Curtains

Specifications

- 61" wide, matt-embossed polyester • 13 oz. or 18 oz. flame retardant vinyl • Heat-sealed and waterproof
- High Temperature – Heavy-Duty Silicone Coated Fiberglass & Acrylic Coated Fiberglass available

Vinyl Laminated Technical Data

Properties:	Test Method	13 oz.	18 oz.
Weight	ASTMD 751-89 sec. 10.2	13	18
Tongue Tear, lbs.	FS 5134 / ASTMD2261		
Warp		90	95
Fill		100	110
Strip Tensile, lbs.	FS 5102 / ASTM D5035		
Warp		240	260
Fill		185	205
Grab Tensile, lbs.	Available upon request		
Warp		240	260
Fill		185	205
Adhesion, lb. 2"	FS 5970 / ASTM D751-18		
Mullen Burst, psi	Available upon request	240	380
Fire Retardant	NFPA-701	Pass	Pass

Colors

13 oz. vinyl – all colors including transparent available | 18 oz. vinyl – all colors



Compliance

California Fire Marshal F-121.2, UL-214 Classified, NFPA-701, ASTM-E84, Class A, MVSS-302

Hardware

A full selection of hardware is available. Please call for details.