

# InsulAir

## Technical Data

<b>Model</b>	<ul style="list-style-type: none"><li>• Insul Air 3 Hp</li><li>• InsulAir 5Hp</li></ul> (all made of G90 galvanized steel)
<b>How Supplied</b>	InsulAir unit, VFD with enclosure, floor and wall mounting hardware
<b>Door Opening</b>	From 5' to 12' wide and from 10" to 16" high
<b>Maximum Air Flow Rate</b>	<ul style="list-style-type: none"><li>• 5 Hp unit - 4500 cfm at 2" static Pressure</li><li>• 3 Hp unit - 2800 cfm at 2" static pressure</li></ul>
<b>Control</b>	VFD manually adjusted
<b>Maximum Noise Level</b>	83 dBA (in middle of door opening)
<b>Maximum Operating Temperature</b>	Cooler to Cooler applications (above 32° F)

## Electrical

<b>Operating Voltage</b>	<ul style="list-style-type: none"><li>• 230 V</li><li>• 460 V</li><li>• 575 V</li></ul>
<b>Drawn</b>	<ul style="list-style-type: none"><li>• 11.8 Amps</li><li>• 5.9 Amps</li><li>• 4.8 Amps</li></ul>
<b>Electric Motor</b>	5 Hp
<b>Circuit Protection</b>	Disconnect switch (supplied by customer)